

DRILLTEC TJP™ **PROTECTORS**



DRILLTEC TJP™ protectors are designed to provide maximum protection for drill pipe and rotary shouldered connections in the harshest of environment.



DRILLTEC TJP™ PROTECTORS

TJP™ FEATURES

- Impact resistant high density polyethylene with PROCADD™ provides superior protection during handling and transportation.
- CNC machined threads offer complete engagement to prevent the protectors from stripping or vibrating off the pipe.
- Offers superior protection to tool joint threads which are susceptible to bi-metal corrosion.
- Complete coverage of seal areas to prevent damage to tool joint faces.



Why compromise your tubular investments? Protect your assets with DRILLTEC™ THREAD PROTECTORS.

All applicable DRILLTEC products are manufactured under strict compliance with API 5CT 9th Edition - Annex I.

Rotary Shouldered Connection Interchangeability chart for API connections

2 3/8" IF
2 7/8" IF
3 1/2" IF
4" FH
4" IF
4 1/2" X-HOLE
4 1/2" IF
5" X-HOLE
5 1/2" FH
6 5/8" FH
6 5/8" REG
NC56
7 5/8" REG

Tool Joint Connection	Pipe Size & Nominal Wt. LB/FT	Interchangeable Connections
NC 26	2 3/8" O.D. 6.65 LB/FT	2 3/8" Internal Flush 2 7/8" Slim Hole
NC 31	2 7/8" O.D. 10.4 LB/FT	2 7/8" Internal Flush 3 1/2" Slim Hole
NC 38	3 1/2" O.D. 13.3 LB/FT	3 1/2" Internal Flush 4 1/2" Slim Hole
NC 40	4" O.D. 14 LB/FT	4" Full Hole
NC 46	4 1/2" O.D. 16.6 LB/FT	4" Internal Flush 4 1/2" Extra Hole
NC 50	5" O.D. 19.5 LB/FT	4 1/2" Internal Flush 5" Extra Hole

Pins:

- (CENL) Closed End Non-Liftable
- (OE) Open end

Boxes:

- (CENL) Closed End Non-Liftable (2 3/8" & 2 7/8")
- (CEL) Closed End Liftable (all others)
- (OE) Open End

